

Model 27-39-60



DATA SHEET

rail | accufiller

Product group - rail | battery filling devices

DESCRIPTION

Model 27-39-60 is designed for automatic central refilling Nickel Cadmium batteries with special hose connectors without moving parts and comes with a 60-litre canister. The device is characterized by being a professional mobile tool with a large capacity for HOPPECKE customers.

The built-in battery has a capacity of 18Ah which gives a device operating time of up to eighteen hours, more than enough for regular maintenance of the batteries. Model 27-39-60 has got also an on-board charger that can charge and maintain the good condition of an 18Ah battery during operation break. The device can be supplied with 230V or 115V AC connections for on-board chargers.

The pump can carry a minimum of 0,6-0,7 liters of water per minute with a maximum pressure of 1,3 bar. The low pressure means that it can perfectly operate on NiCd batteries' central waterfilling systems.

FUNCTIONS

- Advanced operation
- Low pressure filling
- Designed for NiCd batteries with a central waterfilling system
- Automatic filling process with automatic stop
- Built-in battery and charger
- Good manoeuvrability

HOPPECKE Baterie Polska Sp. z o.o.
ul. Logistyczna 10
63-006 Śródka
Poland
Tel.: +48 61 64 65 000
Fax: +48 61 64 65 001
E-Mail: info@hoppecke.pl

