



DATA SHEET

trak | accufiller basic

Product group trak | battery filling devices







DESCRIPTION

Models 10 of trak | battery filling devices series are available in two versions for central and/or manual single-cell filling. These devices are mobile semi-professional equipment, usually used for the maintenance of 1-5 batteries.

Model 10-32 is designed only for central water filling with a battery hose connector. Model 10-72 is designed also for central water filling with a battery hose connector, but additionally, there's an option for single-cell filling with a unique, 14 mm nozzle, filling pistol. Both models come with a 60-litre canister. The built-in battery has a capacity of 7,2Ah which gives a device operating time of up to five hours, more than enough for regular maintenance of the batteries. Models 10 have got also an on-board charger that can charge and maintain the good condition of a 7,2Ah battery during operation break.

Model 12-30 is stationary, very simple and dedicated to central water filling. This device is designed for a constant 230V AC connection without a battery inside. The device should be mounted on the wall, usually beside a battery charging station and it is therefore most suitable for customers with only 1-2 batteries or trucks. Model 12-30 needs the water canister placed underneath it (which is not a part of

DO NOT USE
THIS MODEL FOR
BATTERY ACID
FILLING!

the product and needs to be ordered separately). The device should be mounted approximately 120 cm above the floor. The pumps of Model 10 BFD series and 12-30 can carry a minimum of three liters of water per minute with a maximum pressure of 0,45 bar. The low pressure means that it can operate on most industrial batteries' central water-filling systems.

FUNCTIONS

- Simple and easy operation
- Designed for most of the plug manufacturers
- ▶ Flow Indicator for central water filling operation
- Possibility of single battery cells filling for model 10-72
- Built-in battery and charger for model 10 series
- Good manoeuvrability for model 10 series
- Stationary use for model 12-30
- ▶ Mains connection required to function for model 12-30

HOPPECKE Baterie Polska Sp. z o.o. ul.Logistyczna 10 63-006 Śródka Polen Tel.: +48 61 64 65 000 Fax: +48 61 64 65 001

E-Mail: sbo@hoppecke.pl

