

## Ladegerätetypenliste / Charger Type list with max. kW

trak® power premium charge Types	Modules	max. -10 %	Nom.	Maximum mains power	AC- fuse	AC- connector voltage [V]	DC- cable [mm <sup>2</sup> ]	Casing dimensions			Weight without packing [kg]	Weight [kg]
		Mains Current [A]	Mains Current [A]	rating [kVA]				H [mm]	W [mm]	L [mm]		
E230 G 24 / 030 B-F14 HO-HF	1	5.0	5.0	1.0	16	Schuko 230V 1~	16	590	310	360	14	19
E230 G 24 / 060 B-F14 HO-HF	2	9.9	9.4	2.1	16	Schuko 230V 1~	25	590	310	360	18	23
E230 G 24 / 090 B-F14 HO-HF	3	14.9	13.9	3.1	16	Schuko 230V 1~	35	590	310	360	22	27
E230 G 24 / 120 B-F14 HO-HF	4	19.8	18.4	4.1	20	CEE 32A 230V 1~	50	590	310	360	26	31
D400 G 24 / 125 B-F14 HO-HF	1	5.7	5.1	3.5	16	CEE 16A 400V 3~	50	590	310	360	22	27
D400 G 24 / 250 B-F14 HO-HF	2	11.3	10.2	7.1	16	CEE 16A 400V 3~	70	590	310	360	31	36
E230 G 36 / 015 B-F14 HO-HF	1	3.4	3.0	0.7	16	Schuko 230V 1~	16	590	310	360	14	19
E230 G 36 / 030 B-F14 HO-HF	2	6.8	6.1	1.4	16	Schuko 230V 1~	16	590	310	360	18	23
E230 G 36 / 045 B-F14 HO-HF	3	10.3	9.1	2.1	16	Schuko 230V 1~	16	590	310	360	22	27
E230 G 36 / 060 B-F14 HO-HF	4	13.7	12.2	2.8	16	Schuko 230V 1~	25	590	310	360	26	31
D400 G 36 / 065 B-F14 HO-HF	1	4.3	3.9	2.7	16	CEE 16A 400V 3~	25	590	310	360	22	27
D400 G 36 / 130 B-F14 HO-HF	2	8.7	7.8	5.4	16	CEE 16A 400V 3~	50	590	310	360	31	36
D400 G 36 / 195 B-F14 HO-HF	3	13.0	11.7	8.1	16	CEE 16A 400V 3~	70	590	470	360	39	44
D400 G 36 / 260 B-F14 HO-HF	4	17.3	15.5	10.8	20	CEE 32A 400V 3~	70	590	470	360	47	52
E230 G 48 / 015 B-F14 HO-HF	1	4.3	3.9	0.9	16	Schuko 230V 1~	16	590	310	360	14	19
E230 G 48 / 030 B-F14 HO-HF	2	8.7	7.8	1.8	16	Schuko 230V 1~	16	590	310	360	18	23
E230 G 48 / 045 B-F14 HO-HF	3	12.6	11.2	2.6	16	Schuko 230V 1~	16	590	310	360	22	27
E230 G 48 / 060 B-F14 HO-HF	4	16.9	15.1	3.5	20	CEE 32A 230V 1~	25	590	310	360	26	31
D400 G 48 / 065 B-F14 HO-HF	1	5.8	5.2	3.6	16	CEE 16A 400V 3~	25	590	310	360	22	27
E230 G 48 / 090 B-F14 HO-HF	6	24.9	23.4	24.9	25	CEE 32A 230V 1~	35	590	470	360	30	35
D400 G 48 / 100 B-F14 HO-HF	2	8.9	8.0	5.5	16	CEE 16A 400V 3~	50	590	310	360	31	36
D400 G 48 / 130 B-F14 HO-HF	2	11.5	10.4	7.2	16	CEE 16A 400V 3~	50	590	310	360	31	36
D400 G 48 / 195 B-F14 HO-HF	3	17.3	15.5	10.8	20	CEE 32A 400V 3~	70	590	470	360	39	44
D400 G 48 / 260 B-F14 HO-HF	4	23.1	20.7	14.4	25	CEE 32A 400V 3~	70	590	470	360	47	52
D400 G 48 / 325 B-F14 HO-HF	5	28.8	26.0	18.0	50	CEE 63A 400V 3~	95	1300	600	430	140	167
D400 G 48 / 390 B-F14 HO-HF	6	34.6	31.2	21.6	50	CEE 63A 400V 3~	95	1300	600	430	148	173
D400 G 72 / 040 B-F14 HO-HF	1	5.3	4.8	3.3	16	CEE 16A 400V 3~	16	590	310	360	22	27
D400 G 72 / 080 B-F14 HO-HF	2	10.6	9.6	6.6	16	CEE 16A 400V 3~	35	590	310	360	31	36
D400 G 72 / 120 B-F14 HO-HF	3	16.0	14.3	9.9	20	CEE 32A 400V 3~	50	590	470	360	39	44
D400 G 72 / 160 B-F14 HO-HF	4	21.3	19.1	13.3	25	CEE 32A 400V 3~	50	590	470	360	47	52
D400 G 72 / 200 B-F14 HO-HF	5	26.6	24.0	16.6	50	CEE 63A 400V 3~	70	1300	600	430	140	167
D400 G 72 / 240 B-F14 HO-HF	6	31.9	28.7	19.9	50	CEE 63A 400V 3~	70	1300	600	430	148	173
D400 G 72 / 280 B-F14 HO-HF	7	37.3	33.5	23.2	50	CEE 63A 400V 3~	95	1300	600	430	155	179
D400 G 72 / 320 B-F14 HO-HF	8	42.6	38.2	26.5	50	CEE 63A 400V 3~	95	1300	600	430	163	186
D400 G 80 / 040 B-F14 HO-HF	1	6.0	5.4	3.7	16	CEE 16A 400V 3~	16	590	310	360	22	27
D400 G 80 / 080 B-F14 HO-HF	2	12.0	10.7	7.4	16	CEE 16A 400V 3~	35	590	310	360	31	36
D400 G 80 / 120 B-F14 HO-HF	3	17.9	16.1	11.2	25	CEE 32A 400V 3~	50	590	470	360	39	44
D400 G 80 / 160 B-F14 HO-HF	4	23.9	21.5	14.9	25	CEE 32A 400V 3~	50	590	470	360	47	52
D400 G 80 / 200 B-F14 HO-HF	5	29.9	26.8	18.6	50	CEE 63A 400V 3~	70	1300	600	430	140	167
D400 G 80 / 240 B-F14 HO-HF	6	35.9	32.2	22.3	50	CEE 63A 400V 3~	70	1300	600	430	148	173
D400 G 80 / 280 B-F14 HO-HF	7	41.9	37.7	26.1	50	CEE 63A 400V 3~	95	1300	600	430	155	179
D400 G 80 / 320 B-F14 HO-HF	8	47.8	43.0	29.8	50	CEE 63A 400V 3~	95	1300	600	430	163	186
D400 G 96 / 25 B-F14 HO-HF	1	4.2	4.2	2.6	16	CEE 16A 400V 3~	16	590	310	360	22	27
D400 G 96 / 50 B-F14 HO-HF	2	8.3	8.0	5.2	16	CEE 16A 400V 3~	16	590	310	360	31	36
D400 G 96 / 75 B-F14 HO-HF	3	12.5	11.7	7.8	16	CEE 16A 400V 3~	25	590	470	360	39	44
D400 G 96 / 100 B-F14 HO-HF	4	16.6	15.5	10.4	25	CEE 32A 400V 3~	50	590	470	360	47	52
D400 G 96 / 125 B-F14 HO-HF	5	20.8	19.2	12.95	25	CEE 63A 400V 3~	50	1300	600	430	140	167
D400 G 96 / 150 B-F14 HO-HF	6	24.9	23.0	15.54	50	CEE 63A 400V 3~	50	1300	600	430	148	173
D400 G 96 / 175 B-F14 HO-HF	7	29.1	26.7	18.13	50	CEE 63A 400V 3~	50	1300	600	430	155	179
D400 G 96 / 200 B-F14 HO-HF	8	33.3	30.4	20.72	50	CEE 63A 400V 3~	70	1300	600	430	163	186
D400 G 120 / 25 B-F14 HO-HF	1	5.4	5.2	3.2	16	CEE 16A 400V 3~	16	590	310	360	22	27
D400 G 120 / 50 B-F14 HO-HF	2	10.4	9.9	6.5	16	CEE 16A 400V 3~	16	590	310	360	31	36
D400 G 120 / 75 B-F14 HO-HF	3	15.6	14.5	9.7	16	CEE 16A 400V 3~	25	590	470	360	39	44
D400 G 120 / 100 B-F14 HO-HF	4	20.8	19.2	13.0	25	CEE 32A 400V 3~	50	590	470	360	47	52
D400 G 120 / 125 B-F14 HO-HF	5	26.0	23.9	16.18	50	CEE 63A 400V 3~	50	1300	600	430	140	167
D400 G 120 / 150 B-F14 HO-HF	6	31.2	28.6	19.42	50	CEE 63A 400V 3~	50	1300	600	430	148	173
D400 G 120 / 175 B-F14 HO-HF	7	36.4	33.2	22.66	50	CEE 63A 400V 3~	50	1300	600	430	155	179
D400 G 120 / 200 B-F14 HO-HF	8	41.6	37.9	25.89	50	CEE 63A 400V 3~	70	1300	600	430	163	186

Jedes Ladegerät ist in 5A-Schritten innerhalb seines Produktspektrums verfügbar!  
Every charger is in 5A-steps available in its product range!

## Kundendienst / Customer Service (+49 180 5229999)

Subsidiary	Service Hotline No.	Subsidiary	Service Hotline No.	Subsidiary	Service Hotline No.
A	(+43) 02236 377377	F	(+33) 01 80240008	UK	(+44) 01782 667305
B	(+32) 01561 8740	H	(+36) 030 4248495	RUS	(+7) 0495 7847705
CZ	(+420) 0737 629001	I	(+39) 00261 290870	US	(+1) 0856 6160032
D	(+49) 02963 61130	NL	(+31) 0344 618235	AP	(+62) 021 8936657
	0800 2467732	PL	(+48) 061 6465032	CN	(+86) 021 62849955
E	(+34) 0902 888006	SK	(+421) 0911 286055	J	(+81) 045 5931135